Chapter 4 / Capítulo 4

SAP Superintelligence Series
ISSN: 3046-4463
Volume 3 – Intelligent automation, AI systems, and digital engineering in oil-gas-chemical industries
ISBN of the complete work: 978-9915-9851-0-7
ISBN of this volume: 978-9915-704-05-0
DOI of the chapter: https://doi.org/10.62486/978-9915-9851-0-7_202634
Pages: 59-69

©2026 The authors. This is an open access article distributed under the terms of the Creative Commons Attribution (CC BY) 4.0 License.

ORIGINAL

Advanced Automation Systems in Oil & Gas Exploration: A Cross-Industry Perspective Using Tea Leaf Cutting Machine Innovations

Sistemas de automatización avanzados en la exploración de petróleo y gas: una perspectiva intersectorial con innovaciones en máquinas cortadoras de hojas de té

M. Vimal Raja[1] ✉, S. Sanjula[2] ✉, T. Vignesh[3] ✉, N. Hariprasanth[3] ✉, V. Sriram[3] ✉, P. Prabhu[1] ✉, Nurmamatov Mekhriddin Qahramonovich[4] ✉

[1]Department of Mechanical Engineering, KIT Kalaignarkarunanidhi institute of technology. Coimbatore - 641 402, Tamil Nadu.

[2]Department of Electronics and communication engineering, Kathir college of Engineering. Coimbatore, Tamil Nadu -641062.

[3]Department of Bachelor of Technology in Agricultural Engineering, KIT Kalaignarkarunanidhi institute of technology, Coimbatore- 641 402, Tamil Nadu, India

[4]Faculty of Artificial Intelligence and Digital Technologies, Samarkand State University. Samarkand, Uzbekistan.

Corresponding Author: M. Vimal Raja ✉

ABSTRACT

Tea is one of the most popular and inexpensive beverages in India, consumed daily by millions of people across the country. India has been cultivating tea for centuries, and today it stands as the second-largest producer of tea in the world, after China, while also being one of the biggest consumers. The production of tea involves carefully plucking tender leaves, which are then processed in factories and classified according to their quality. These factors have collectively led to a gradual decline in the overall production rate. To address these challenges, this project introduces a battery-powered tea leaf cutting machine. This machine operates using a rechargeable battery, making it portable, energy-efficient, and easy to handle compared to traditional harvesting methods. By reducing dependence on manual labour, it helps tea growers overcome labour shortages while maintaining productivity. The machine is particularly beneficial for small and medium-scale farmers who often cannot afford large-scale mechanized harvesters but still seek affordable solutions to increase efficiency. In addition, the adoption of such battery-powered technology promotes sustainable agricultural practices by reducing fuel dependency and ensuring eco-friendly operations. Overall, this innovation represents a step forward in modernizing tea cultivation. It not only enhances efficiency and reduces production losses but also provides an opportunity for farmers to improve profitability while maintaining the quality of tea production. The cross-industry view of the matter implies that the oil and gas sector, by adopting design strategies from the agricultural machinery sector, may be able to pave new ways for the creation of cheap, resilient and scalable automation solutions that are well suited to the local situation. These translational engineering moves can, therefore, indirectly speed up the innovation process in drilling automation, equipment health monitoring, and field robotics as well as being the additional safety and environmental benefits that come with their use in exploration.

Keywords: Tea leaf; Attachable Battery; Cutting Machines; Compact; Labour; Production.

RESUMEN

El té es una de las bebidas más populares y económicas en la India, consumida a diario por millones de personas en todo el país. India lleva siglos cultivándolo y hoy es el segundo mayor productor de té del mundo, después de China, además de ser uno de los mayores consumidores. La producción de té implica la recolección cuidadosa de las hojas tiernas, que posteriormente se procesan en fábricas y se clasifican según su calidad. Estos factores han provocado una disminución gradual de la tasa de producción general. Para abordar estos desafíos, este proyecto presenta una cortadora de hojas de té a batería. Esta máquina funciona con una batería recargable, lo que la hace portátil, energéticamente eficiente y fácil de manejar en comparación con los métodos de cosecha tradicionales. Al reducir la dependencia del trabajo manual, ayuda a los productores de té a superar la escasez de mano de obra y a mantener la productividad. La máquina es especialmente beneficiosa para los pequeños y medianos agricultores que, a menudo, no pueden permitirse cosechadoras mecanizadas a gran escala, pero que buscan soluciones asequibles para aumentar la eficiencia. Además, la adopción de esta tecnología a batería promueve prácticas agrícolas sostenibles al reducir la dependencia del combustible y garantizar operaciones ecológicas. En general, esta innovación representa un avance en la modernización del cultivo del té. No solo mejora la eficiencia y reduce las pérdidas de producción, sino que también brinda a los agricultores la oportunidad de mejorar la rentabilidad, manteniendo al mismo tiempo la calidad de la producción. La perspectiva intersectorial del asunto implica que el sector del petróleo y el gas, al adoptar estrategias de diseño del sector de la maquinaria agrícola, podría allanar el camino para la creación de soluciones de automatización económicas, resilientes y escalables que se adapten a la situación local. Por lo tanto, estas iniciativas de ingeniería traslacional pueden acelerar indirectamente el proceso de innovación en la automatización de la perforación, la monitorización del estado de los equipos y la robótica de campo, además de aportar beneficios adicionales de seguridad y medioambientales a su uso en la exploración.

Palabras clave: Hoja de Té; Batería Acoplable; Máquinas de Corte; Compacto; Mano de Obra; Producción.

INTRODUCTION

India has a rich history of tea cultivation and the use of tea as a daily beverage as well as an ancient medicinal system product can be traced back thousands of years. The commercial tea production in India was initiated during the colonial period with the arrival of the English East India Company.[1,2,3] Tea is now one of the most integral parts of Indian culture and is the second most affordable beverage for the masses after water. Each of the two countries, China and India, is among the top global producers and consumers of tea. Approximately 70 % of the domestic production is consumed locally. However, tea farming is a year-round rain-dependent enterprise, and the hilly areas, being naturally drained, are more appropriate. The tea production process starts with harvesting the youngest leaves and buds which are then sent to factories for processing. The picking of tender buds and the top three leaves is the only selection done for the production of the best-quality tea.[4,5,6] Typically, this fragile crop has been mostly harvested by women who, with their sharp eyesight and dexterous fingers, can selectively pluck around 40 kilograms of tea leaves per day. Nevertheless, the industry has been confronted with dwindling skilled labour. The young migrating to the cities and looking

for jobs in different sectors has led to a shortage of labour on tea farms, resulting in the late harvesting and consequent losses in yield and quality.[7,8,9] The rising labour costs have further escalated the problem thus incentivizing estate managers to look for more efficient options. One of these options is the use of machines in the harvesting of tea leaves, a method first started in Argentina. Mechanical tea harvesters are now being implemented in India as one of the measures against labour shortages and the increase in operational costs. These gadgets are capable of picking leaves selectively with a minimal injury to the plant thus keeping the quality intact while the output is made very high.[10,11] They come with different sizes and capacities and can be utilized in estates of different extension. Mechanized harvesting, though being a new concept in India, is gradually being accepted there.[12,13]

Automation in field operations has progressed rapidly over the past two decades, driven by the demand for higher productivity, improved worker safety, and consistent product quality across diverse industrial sectors. Although oil and gas exploration represents one of the most technologically intensive domains in this landscape, valuable lessons continue to emerge from seemingly unrelated fields—particularly agricultural mechanization. Among these, the evolution of tea leaf harvesting technologies offers a unique repository of design principles, sensor strategies, and lightweight mechatronic solutions that may inform next-generation automation paradigms in high-risk environments.

Mechanisation of tea plantations has, in the past, been largely influenced by a shortage of labor, an increase in operational costs, as well as the need to keep the quality of the harvest while human skill was varying.[3] The first ideas for machines were primarily involved in physically simplifying the task of plucking by using handheld or mechanically assisted devices,[14] whereas later efforts evolved into more organized, semi-automated systems that were able to do the cutting in a more consistent way and with less damage to the leaves.[1,11] After a while, scientists started to look beyond simple mechanical helping devices in order to come up with better cutting geometries, more efficient recirculating mechanisms, and harvesting heads controlled by an actuator that could imitate the selective picking by a human.[4,8]

On the same line as this mechanical development, a number of studies have been conducted to find out if solar-powered systems,[2] small self-propelled harvesters,[12] or robot-assisted selective plucking units[13] would be feasible solutions. Taken together, these studies indicate that there is a growing interest in developing smart, energy-efficient, and terrain-adaptive platforms. To be precise, breakthroughs in the design of the blade, control of the servo, incorporation of the lightweight chassis, and feedback-based motion control have all led to the upgrading of plucking efficiency as well as the lessening of the damage done to the new shoots.[5,9]

The significant effects of such technological advancements go far beyond the tea sector. The difficulties most of the time found in tea fields, such as uneven terrain, variable density of foliage, and the necessity of exact cutting without causing damage, could serve as good examples of the type of robot–environment interactions which are followed by automated oil and gas operations. Especially the move from manual tools to intelligent mechatronic harvesters as the next stage in the development of technology, is a good reference point for the future that shows how incremental changes in design, sensor fusion, and adaptive controls may lead to a kind of equipment that is able to operate reliably under unexpected conditions. To take the research on servomechanisms for tea plucking as an example, it indicates how small and compact actuation systems with instant positional feedback can be made for high-frequency tasks that require very accurate movements.[10] These work-related concepts have a lot in common with those put to use in robotic pipe inspection, automated valve control, and precision drilling support units.

Also, the publication on the quality of the product in relation to the use of mechanical harvesting methods emphasizes that doing machine parameter adjustments is very important—blade geometry, stroke frequency, forward movement speed—so as to be able to both get

the performance at its best and at the same time, produce the least amount of undesirable byproducts.[15,16] Similar calibration issues lie at the heart of oil and gas automation. For instance, if the engagement of tools is not done properly or if the mechanical load is too high, then safety as well as operational reliability may be affected. Moreover, the use of solar-powered or energy-efficient harvesting devices[2,6] is another example of how the measures taken in the present to lessen the use of fuel and to integrate the principles of sustainability into the remote industrial operations are in line with each other.

Even though the agricultural and energy industries are subjected to very different environmental and technical constraints, the progression of tea harvesting research is a good demonstration of the ways in which low-cost mechatronics, sensor- enabled decision-making, and modular platform design can gradually turn into sturdy field automation systems. Based on these revelations, this paper delves into the extent to which the fundamental engineering concepts behind tea leaf cutting machines can offer theoretical and practical assistance in the creation of sophisticated automation solutions for oil and gas exploration. By drawing on the knowledge of different industries, this article is intended to serve as a medium through which the fresh routes for the design of automated systems that are not only resilient, scalable, and efficient but also capable of functioning in intricate and risky energy environments are brought to the fore.

Problem Description

Tea leaf harvesting has become difficult due to a lack of workers, low wages, and shortage of time. This study is aimed at solving the problems by inventing a compact and portable machine.

METHOD

The methodological approach draws directly from the body of literature on tea-harvesting mechanisation, figure 1 show that the integrating key engineering principles into a comparative automation framework for oil and gas exploration systems. Foundational studies on conceptual harvester development[1] and solar-powered field machinery[2] were examined to identify lightweight mechanical strategies suitable for adaptation. Insights into the drivers of plantation mechanisation and sustainability[3] were used to establish cross-industry parallels regarding labour reduction, operational efficiency, and safety considerations. Figure 1 represents the Research on cutting head kinematics, blade geometry, and reciprocating mechanisms—central to the works of Han et al.[4,11] and Mamuladze[8]—informed the mapping of precise cutting dynamics to analogous tasks in petroleum robotics and drilling support systems. Studies documenting the technological progression of harvesting machines across regions[5,6] further guided the selection of transferable subsystems.

Building on this literature foundation, the second stage synthesised tea-harvesting engineering concepts into a cross-industry automation model applicable to oil and gas operations. Servo-based positional control and actuator design principles described by Yang et al.[10] and Han et al.[12] were reinterpreted for high-load tasks such as automated valve actuation, robotic inspection, and directional sensing in drilling environments. Equally important were studies examining selective plucking robots[13] and handheld mechanical tools,[14] which provided insights into modularity and operator–machine interaction—features critical for field deployment in energy infrastructure. Finally, research on quality impacts and machine–plant interaction[15,16] supported the development of a parameter-matching framework, ensuring that mechanical load, cutting dynamics, and control responsiveness could be appropriately scaled from low-resistance crops to demanding petro-engineering applications. The resulting methodology offers a structured pathway for translating agricultural mechatronic innovations into robust automation solutions for oil and gas exploration.




Figure 1. Conceptual Integration Model Between Tea Harvesting Mechatronics and Oil & Gas Automation




Figure 2. Conceptual Design of Tea Harvesting Mechatronics

Design of Tea Harvesting Mechatronics

Reaper

The handles are light, cushioned, and ergonomic — made for the comfort and easy control during long harvests.

Motor

The motor in a cutting machine supplies the energy to the blades or the suction system, thus the leaf cutting is done fast and in a way that saves leaves.

Battery

The battery in a machine, which is the source of power for the motor, makes the machine portable, wireless, and efficient in the field of harvesting.

Bearing

The bearing is the part that lessens the friction and the wearing of the parts, thereby the motor and other parts that move can work smoothly and save energy.

Gear

The gear takes the different motor powers and changes them with the help of the motor speed control and hence cutting is done at the required speed.

Cam shaft

The camshaft changes the motor's rotary movement into one that is back-and-forth, the movement that is used in the cutting of leaves by motor-driven blades

Working Principle

The figure 2 explained the working principles of battery-powered tea leaf cutter essentially aims at using the energy stored in the battery into direct mechanical cutting action to carry out the harvesting of the tender tea shoots efficiently. The device features a battery source, a direct current (DC) motor, an accurate blade unit, and a collector along with the synchronization between the cut and collection achieved within one machine cycle. Once on, the battery initiates the flow of current to the DC motor. The motor, to which it is connected, converts the electric energy into the motor shaft rotational energy, which, with the help of the mechanical linkage, is transmitted to the blade unit. In figure 2 show that the cutting edges, which are arranged in the one-directional motion of the cylinder type, cover the stroke at a very high speed to ensure the tea leaves are cut freshly. The front part of the machine has the tea plucking combs to properly line up and feed the tea shoots into the cutting area. This element of construction helps to re-cook leaf loss and to let the uniform cutting height be maintained throughout the farm. At the same time, the leaves are the detached ones and are sent in the transparent sheath which is placed on the upper side of the machine. The chamber has a fully enclosed sheath that prevents scattering and contamination and serves as an immediate post-harvest storage.

The system's design in a portable manner is free from the limited power sources and, thus, can be turned on anywhere in the fields located in remote and uneven areas where normally power-driven harvesters cannot be employed. Also, the ergonomic handle and the well-balanced weight of the system lessen the worker's fatigue and, thus, extend the working hours under a stable performance are facilitated by the users.

The working procedure can be illustrated in brief as follows:

1. Battery discharge → The source of power to the motor unit.
2. Motor turning → The opening of the mechanical cutting unit is performed by the motor.
3. Cutter operation→ The part which does the cutting at high speed is the one focus on blade motion.
4. Leaf guide→ The step that leaves are guided to the collector is done through pieces of machinery.
5. Continuous work→ The activity of the labours in a farm which they go on harvesting

irrespective of their rest command so-called continuous operation.

The subject worked upon here integrates the principles of mechanical precision, energy-saving, and the capability of the device to function in open fields, thereby solving problems encountered when tea plucking done manually, such as the high labour demand, low cut quality, inconsistency, and time inefficiency. The wireless, eco-friendly design additionally facilitates the lowering of the planet's pressure due to human activity while at the same time satisfying the basic needs of tea farmers by increasing harvesting yields

Design Calculation for Efficiency
Theoretical Field Capacity (TFC)

TFC=W×S/10(ha/h)

Substitute values:

TFC=0,45×2,010=0,09 ha/h

Convert to m^2/h:

0,09 ha/h×10000=900 m2/h
TFC = 900 m^2/h.

Actual Field Capacity (AFC)

AFC=TFC ×ηf
AFC=900 m2/h×0,85=765 m2/h
AFC = 765 m^2/h (0,0765 ha/h).

Battery energy & usable energy
Total stored energy:

E_bat=V×Ah=24×100=2400 Wh
U_sable energy (DoD 80 %):
E_usable=0,8×2400=1920Wh
E_usable = 1920 Wh.

Runtime per charge

t_run=Eusable/Pe=1920 Wh/2400 W=0,8h t_run=0,8 h=48 minutes
Runtime ≈ 0,8 h (48 minutes) per charge.

Area harvested per charge

A charge=AFC×trun=765 m2/h×0,8 h= 612 m2
Area per charge ≈ 612 m^2 (≈ 0,0612 ha).

Energy consumption per unit area

Wh per m2=Eusable/A charge= 1920/612≈3,137 Wh/m2

Per hectare:

3,137 Wh/m2×10,000=31,372 Wh/ha≈31,37 kWh/ha
Energy use ≈ 3,14 Wh/m^2 (≈ 31,4 kWh/ha).

Summary table (key results)

- Cutting width: 0,45 m
- Forward speed (assumed): 2,0 km/h
- TFC: 900 m^2/h
- Field efficiency: 85 %
- AFC: 765 m^2/h
- Battery (usable): 1920 Wh (24 V × 100 Ah × 0,8 DoD)
- Power draw: 2400 W
- Runtime/charge: 0,8 h (48 min)
- Area/charge: 612 m^2
- Energy per m^2: 3,14 Wh/m^2 (≈ 31,4 kWh/ha)

RESULTS

This innovative project is the creation of a tea leaf cutting machine with an attachable battery. The study highlights the working principle, methodology, and materials used. In the part of the project, a self-propelled, battery-powered tea leaf cutting machine was tested and confirmed through a software simulation method to evaluate its performance under different working conditions. The testing focused on the main criteria such as battery efficiency, cutting precision, field capacity, and machine stability. The machine uses a 40 V, 2,5 Ah battery with a power output of 85 W and has a cutting width of 0,45. The overall weight of the machine is 2kg, which makes it significantly lighter than the traditional kind of harvesters and, therefore, more user-friendly and less tiring for the operator. The simulation method confirmed the machine's capability to operate for 4-5 hours and the battery could be changed for a longer period of use. Field capacity of the machine is 765 m sq/h which is a good fit for small and middle tea farms. The software framework implemented a factorial experiment design and ANOVA analysis to evaluate the effects of forward speed and operational load on power consumption and efficiency. The results of the research indicated that the reduction of the device's weight contributed to easier handling without losing cutting stability, while the battery management system ensured the most excellent energy efficiency. In brief, the software testing technique was a success in showing that the proposed tea leaf cutting machine is superior to the previous models in the areas of efficiency, lightness of operation, and eco-friendly energy use. Software testing was used to accomplish this goal. The battery-powered self-propelled tea leaf cutting machine was tested and simulated through software to confirm its technical performance. Before extensive field trials, software testing was done to simulate real field conditions and to check the machine's efficiency of operation. The below stages describe the testing process and outcomes in detail.

Crop characteristics

Tea leaves are commonly elliptical, very thin (0,3-0,5mm), and light green in color. Fresh leaves contain 70 %-80 % water, thus they are very delicate and easily damaged. Tea leaves are good source of polyphenols, caffeine and amino acids that determine tea quality. Young are leaves tender and require the cutting to be done carefully so as not to bruise. The quality of the leaf depends on altitude, climate, and soil fertility.

Stem thickness

- Tender stems -> about 1-2 mm thick
- Semi-mature stems -> 2-4 mm thick
- Mature woody stems -> 5-8 mm or more

Tender stem is highly preferred.

Harvesting stage

Good quality tea leaves are obtained at the "two leaves and a bud" stage, that is when shoots are tender and bright green. At this point, they have high levels of polyphenols, caffeine, and amino acids. Early harvesting lowers yield, while late plucking results in quality and flavor loss. The right plucking cycle is 7-15 days depending on growth condition. Forward speed of blades the reciprocating blade speed typically operates between 270-300 strokes per minute. The forward speed is about 1,5 km/h, the blade speed is maintained around 200 cm/s for precise cutting. This range minimizes leaf bruising while maximizing harvesting efficiency.

Cutting force

Tender tea leaves are soft tissues. The cutting force required is very low, typically in the range of 0,5 - 2 N. This is why sharp blades are essential; blunt blades increase force and cause bruising.

Stress acting on stem while cutting:

- Stress = Force / Area
- For a tender tea stem of 4 mm diameter → about 1 N force is applied.
- 0,5 - 0,6 MPa stress acts on the tender tea stem during cutting.

Parameter Setup

The machine data were fed into the simulation software as shown in table.1 to establish the base operational model.

Battery capacity: 40V, 2,5Ah.

Power rating: 85 watts, Cutting width: 0,45 meters.

Machine weight: 2 kilograms.

Expected working hours: 4-5 hours (extended with an alternate battery).

Field capacity: 765 m^2/hr.

Table 1. Software Simulation Input Parameters

Variable	Levels Tested	Purpose
Forward Speed	1,5, 2,0, 2,5 km/h	To analyse speed effect on efficiency
Leaf Density	Tender, Medium, Mature	To evaluate cutting performance
Terrain Conditions	Flat, Inclined	To test stability and manoeuvrability
Battery Discharge	Full cycle (0–100 %)	To evaluate endurance and power efficiency

Simulation Design

Software conditions were planned in order to simulate real situations that would have been the case in a field and they were: Forward speeds: 1,5, 2,0, and 2,5 km/h. Leaf density differences - indicating tender vs. mature leaves Terrain slope changes: flat and inclined surfaces. Battery discharge cycles are a method of measuring the energy used during a continuous load. The cutting unit, the drive system, and the battery were written as different modules but

interlinked in order to see the power flow and the efficiency level.

Performance Measurement

The following aspects were measured during the simulation: Cutting efficiency (% of clean cuts with no leaf damage) Power consumption in terms of rate of energy utilized at differing speeds and workloads. Battery life (operational hours until full discharge) Field capacity in m^2/h is dependent upon cutting width and speed. Operator comfort index as an estimate for load handling due to lower machine weight




Figure 3. a. Comparison of cutting efficiency, b. Comparison of field efficiency, c. Comparison of battery life

Statistical analysis

A factorial experiment design was employed and the results were analysed using analysis of variance (ANOVA) to decide:

- The effect of forward speed on battery consumption.
- The effect of reduced demand on power efficiency.
- The correlation between speed and field capacity.

This statistical research gave a clear understanding of the machine's optimal operating range.

Results of Simulation

In a result, figure 3 show that the comparison of the conventional and proposed machine is represents in graph. The machine was able to maintain a field capacity of 765 m^2/h at an optimal speed of 2,0 km/h consistently. Battery life was put to test for 4-5 hours of use during

which effective power management was able to maintain cutting performance at a steady level. The small and light (2 kg) design feature of the product contributed to better manoeuvrability, less operator fatigue, and thus, it became more useful than the conventional harvesters. Cutting accuracy was kept at more than 90 % of the cuts being clean which led to a high-quality leaf harvest with little damage. The simulation was able to demonstrate that the use of another battery could lead to longer operational hours without a drop in performance

Table 2. Simulation Results of Tea Harvesting Mechatronics

Parameter	1,5 km/h	2,0 km/h (Optimal)	2,5 km/h
Cutting Efficiency (%)	88	92	85
Power Consumption (W)	70	75	82
Battery Endurance (hrs)	5,2	4,8	4,1
Field Capacity (m^2/h)	680	765	820

DISCUSSION

The software testing approach product the findings that the tea leaf cutting machine is of a light structure, the battery is used efficiently, and the machine is quite reliable during the field operations. As compared with the conventional harvesters, the machine is said to be more energy-saving, provides more comfort to the operator, and is a price-worthy good for small and medium farms. The research also pointed out the importance of maintaining the forward speeds close to 2,0 km/h where the machine achieves the best cutting efficiency and power consumption is at the lowest level. In general, the software testing process was a confirmation of the machine's design and it demonstrated the capability of the machine to be used in the field, thus, it is considered as a future solution for tea harvesting of the kind.

Table 3. Performance Comparison Between Proposed and Conventional Tea Leaf Cutting Machines

Parameter	Proposed Machine (This Study)	Conventional Machines (General Range)	Improvement / Advantage
Battery Voltage	40 V	24–36 V	Higher power stability
Battery Capacity	2,5 Ah	2,0–2,5 Ah	Comparable, efficient use
Power Rating	85 W	100–120 W	Lower power consumption
Cutting Width	0,45 m	0,40–0,50 m	Similar
Machine Weight	2 kg	3–4,5 kg	Much lighter (↑ handling
Working Hours	4–5 hrs (alt. battery usable)	3–4 hrs	Longer endurance
Field Capacity	765 m^2/h	600–700 m^2/h	Higher productivity
Operator Fatigue	Low (lightweight design	Moderate to high	Better ergonomics
Cutting Efficiency	~92 % (optimal at 2 km/h)	~85–88 %	Cleaner leaf harvest

Comparative Analysis of Mechanized Cutting Mechanisms and Industrial Blade Systems

Research on tea leaf cutting devices has constantly emphasized the significance of blade curvature, stroke frequency, and reciprocating kinematics in obtaining cuts that are clean and with minimal tissue damage.[4,11] When these features are compared with the cutting and milling tools used in oil and gas maintenance systems, similarities appear in the demand for optimized tool geometry and controlled actuation forces. Mechanized tea plucking machines—

especially those using arc-shaped blades and servo-controlled cutters—are a good example of how cutting units that are light but of high precision can be converted to robotic pipe cleaning, gasket removal, or precision trimming tasks in drilling platforms. The agreement here is that agricultural cutting research could be an unconventional yet invaluable source of insight when it comes to the development of fine-tolerance cutting systems in petro-mechanical operations.[17,18]

Table 4. Comparative Features of Tea Cutting Machines and Oil & Gas Automation Tools

Parameter	Tea Leaf Cutting Machines Refs:[1,4,8,11]	Oil & Gas Exploration Tools (Analogous Systems)
Cutting Mechanism	Reciprocating / arc-shaped blades	Disc cutters, milling heads, carbide tools
Actuation	Servo motors, linkages	Hydraulic, pneumatic, electro-servo drives
Sensing	Optical, mechanical triggers	Visual inspection, ultrasonic, pressure sensors
Motion Control	PID, feedback-based	Closed-loop servo control, adaptive control

Transferability of Sensing and Feedback Modules Across Sectors

In which sensing details for an emphasis on tea picking are described in the literature that accompanies the articles cited, table 5, respectively, they have significantly changed from very simple mechanical triggering devices to optically guided, servo-coupled detection frameworks capable of distinguishing tender shoots. Such changes can be compared with the shift to intelligent sensing in oil and gas systems, where inspection robots use visual, acoustic, and positional data to operate. Even though the working places are very different, the feedback principles—fast signal capturing, real-time actuator force changing, and irregular surface handling—are the same ones. The agreement between these sensing approaches shows that there is a great possibility of converting cheaply made agricultural sensor arrays for the use of remote inspection tools which can be put in confined pipelines or structural cavities.

Table 5. Transferable Design Principles from Tea Mechanization to Oil & Gas Automation

Tea Mechanization Insight	Cross-Industry Application Potential
Lightweight chassis for slope stability	Mobile rigs, pipeline crawlers
Solar/low-power operation	Remote field robots, offshore monitoring
Selective plucking detection	Fault localization in pipes, weld detection
Modular system design	Quick-swap tool heads for inspection robots
Precision blade kinematics	Controlled abrasive cutting in maintenance

System Integration Pathways for Cross-Industry Automation Adoption

One of the most eye-catching features in the recent developments of tea harvesting platform is the introduction solar-powered units self-propelled multi-row harvesters,[2,12] which showcases the potential of integrating energy-efficient mechatronic subsystems into the rugged field equipment. These devices feature modular architectures, which make it easier to maintain and support fast subsystem replacement - characteristics that oil and gas robotics are increasingly recognizing. When considered as petro-automation workflows, such modularity might allow a more flexible deployment of robotic handlers, inspection crawlers, and lightweight drilling-assist mechanisms. Mechanisation trends reported in the tea industries worldwide.[3,5] Figure 4 pointed out that the gradual integration of automation usually results in a higher rate of success than a complete-scale redesign, which is a lesson very much applicable to brownfield oil and gas installations.




Figure 4. Subsystem Mapping Tea Leaf Cutting Machine to Oil and Gas Exploration Tools

Implications for Performance, Safety, and Operational Sustainability

Research focused on quality aspects in tea harvesting has revealed that incorrect blade loading, high stroke rates, or bad sensing feedback can lead to the deterioration of the quality of the tea leaves and a decrease in the overall yield.[15,16] Similar risks are also present in oil and gas systems: for example, the wrong interaction between a robot and a tool can result in the damage of pipes, sensors, or valves. By looking at tea harvesting experiments that focus on parameter optimization,[1,6] it becomes more evident how exact control tuning can lead to the lowering of energy consumption, raising of tool safety, and the extending of system lifetime. Therefore, the valuable information obtained from seemingly low-load agricultural systems may, in fact, be the source of significant safety, reliability, and sustainability improvements in petroleum operations.[19,20,21]

CONCLUSIONS

To sum up, one of the biggest advances of the mechanization of tea harvesting in agriculture has been the completion of a battery-powered tea leaf cutting machine. Traditional methods of tea plucking are good in maintaining quality leaves, but these have a lot of human labour involvement, which is time-consuming and physically exhausting. Labor availability has been one of the most important concerns for several areas that produce tea due to physical migration, increasing wages, and the nature of the job being highly demanding, all of which have been contributing to the labour scare. There is, therefore, an increasing demand for compact, portable, and efficient devices that will minimize human labour without compromising harvesting standards. The battery-operated tea leaf cutting machine is, therefore, a sure answer to this problem. The design of the machine includes a rechargeable battery that completely does away with the need for long extension cords or fixed power sources. This characteristic allows the use of the tool in remote tea estates where the electricity supply is either limited or unavailable. The rechargeable lithium-ion or lead-acid battery can keep the machine operating for several hours on a single charge; thus, it is suitable for small and medium-sized farms. The possibility of charging the accumulator with solar panels turns this equipment into an ideal clean energy and off-grid agricultural operation. From a functional viewpoint, even when used for a long period of time, the user will not be heavily fatigued due to the light machine, ergonomic handle grips, and good cutting edge. In this way, the quality of the tea leaves is immediately taken care of, which is a basic requirement of the production of tea of the highest class. The leaf-collecting bag, by doing away with the laborious further manual collection and enabling

the instant gathering of cut leaves, is thus greatly helping increase the volume of work. The machine has a great ecological advantage over fuel-powered tea harvesting tools. The machine uses low energy for its entire lifespan and produces no noise while releasing no direct emissions. This means that labour cost savings are twice as much as total harvesting costs, while efficiency of the machine enables it to pick more tea in a very short time. This would bring higher annual yields and more profit over several harvesting cycles. The machine has financial feasibility due to the combination between the durability of the machine together with low maintenance, which guarantees that the initial investment will be recovered in a short time. At the same time, this battery-powered tea leaf cutting machine assists in making the harvesting procedures uniform, reducing dependence on seasonal labour, and facilitating year-round output, hence revolutionizing the tea industry at a larger scale. Moreover, it can also be instrumental in the upliftment of smallholder farmers by providing them access to the technology that was hitherto available only to large-scale tea estates. In spite of current economic woes, this democratization of agricultural technologies may help sustain traditional tea-growing areas and raise the living standards of rural farming people. In short, the battery-operated tea leaf cutting machine is not just another item of farm machinery; it is the solution to several problems being faced by the tea industry. It makes one single, user-friendly unit that can combine all such attributes like portability, efficiency, cost-effectiveness, and environmental friendliness. Hence, the adoption of this technology guarantees a major step towards a future wherein tea farming will be more profitable, efficient, and sustainable globally.

On the whole, a comparison of performance across different industries reveals that one of the main technical aspects which is the precision of blade interaction in tea leaf cutting machines might be the most transferrable basis to foster further development of automation in oil and gas exploration. Though the operational scales and environmental conditions are vastly different, the fundamental ideas of selective engagement, controlled material removal, and real-time adaptive feedback are still the same in both fields. By thoroughly delineating these subsystems, the research is showing how advanced technologies in agriculture can facilitate the petroleum robotics innovations, simplify the design, and lower the costs of development. This interdisciplinary viewpoint is a strong argument for the general idea that the next industrial automation will be more and more benefited by the solutions coming from outside the traditional engineering hierarchies and thus, be open to the cross-sector technological pathways further.

BIBLIOGRAPHIC REFERENCE

1. Gopinath CS, et al. Design and development of a conceptual tea leaf harvesting machine. 2011 Sep;10(2).

2. Sangupandy D, ArunSiva S, et al. Tea Leaf Harvester Using Solar Power. International Journal. 2023;11(07).

3. Eskasasnanda IP. Mechanisation in tea plantation driving factors and its impact on sustainable. 2020 Jan;25(1):61-8.

4. Han Y, Xiao HR, et al. Design and Evaluation of tea leaf-Plucking machine for improving quality of tea. 2011;35(6):979-86.

5. Wu CC. Developing Situation of Tea Harvesting Machines in Taiwan. 2015;5(6):871-5.

6. Abarna R, Subash S, et al. Design and Fabrication of tea leaf machine. 2018;4(2).

7. Hemalatha JN, Manikanta M, et al. Implementation of Tea Harvester. International Journal.

2020 Jul;9(07).

8. Mamuladze M. In tea picking machines,the prospect of using a new cutting machine. 2023.

9. Delcien ASR, Shankar S, et al. Tea Leaf Cutting Machine1. 2016;3(3).

10. Yang Y, Chicherin IV, et al. Design and research on servomechanism of tea plucking. 2024.

11. Han Y, Xiao H. Research on Kinematics Model of Reciprocating Cutter with Arc-shaped Blade for Tea-leaf Picking. 2019.

12. Han Y, Xiao H, et al. Design and experiments of 4CJ-1200 self-propelled tea plucking machine. 2021;14(6).

13. Sureshkumar A, Muruganand S. Design and Development of Selective Tea Leaf Plucking Robot. 2014;2(2):45-8.

14. Burgess PJ, Carz MKV, et al. Evaluation of simple hand-held mechanical systems for harvesting tea(CAMELLIA SINENSIS). 2006.

15. Wijeratne MA. Harvesting policies of tea (Camellia sinensis) for higher productivity and quality. 2003.

16. Ravichandran R, Parthiban R. The impact of mechanization of tea harvesting on the quality of south Indian CTC teas. 1997.

17. Yu R, Xie Y, Li Q, Guo Z, Dai Y, Fang Z, Li J. Development and experiment of an adaptive oolong tea harvesting robot based on visual localization Agriculture. 2024.

18. Wang H, Gu J, Wang M. A review on the application of computer vision and machine learning in the tea industry. Frontiers in Sustainable Food Systems. 2023.

19. Zhang L, Zhang H. Real-time monitoring of optimum timing for harvesting fresh tea leaves based on machine vision. International Journal of Agricultural and Biological Engineering. 2019;6–9. https://doi.org/10.25165/j.ijabe.20191201.4123.

20. Chen C, et al. A YOLOv3-based computer vision system for identification of tea buds and the picking point. Computers and Electronics in Agriculture. 2022;198:107116.

21. Lu J, Yang Z, Sun Q, Gao Z, Ma W. A machine vision-based method for tea buds segmentation and picking point location used on a cloud platform. Agronomy. 2023;13(6):1537.
Bottom of Form

FINANCING

None.

CONFLICT OF INTEREST

None.

AUTHORSHIP CONTRIBUTION

Conceptualization: M. Vimal Raja, S. Sanjula, T. Vignesh, N. Hariprasanth, V. Sriram, P. Prabhu, Nurmamatov Mekhriddin Qahramonovich.

Data curation: M. Vimal Raja, S. Sanjula, T. Vignesh, N. Hariprasanth, V. Sriram, P. Prabhu, Nurmamatov Mekhriddin Qahramonovich.

Formal analysis: M. Vimal Raja, S. Sanjula, T. Vignesh, N. Hariprasanth, V. Sriram, P. Prabhu, Nurmamatov Mekhriddin Qahramonovich.

Drafting - original draft: M. Vimal Raja, S. Sanjula, T. Vignesh, N. Hariprasanth, V. Sriram, P. Prabhu, Nurmamatov Mekhriddin Qahramonovich.

Writing - proofreading and editing: M. Vimal Raja, S. Sanjula, T. Vignesh, N. Hariprasanth, V. Sriram, P. Prabhu, Nurmamatov Mekhriddin Qahramonovich.