Chapter 04

Advanced composite materials, biopolymers, and additive manufacturing for oil-gas-chemical engineering
ISBN: 978-9915-704-06-7
DOI: 10.62486/978-9915-704-06-7.Ch04
Pages: XX-XX

©2026 The authors. This is an open access book distributed under the terms of the Creative Commons Attribution (CC BY) 4.0 License.

Automation-Enabled Engineering Futures: Linking Oil-and-Gas Innovation with Renewable Biopolymer Feedstocks for Additive Manufacturing

El futuro de la ingeniería basada en la automatización: vinculando la innovación en el sector del petróleo y el gas con las materias primas biopoliméricas renovables para la fabricación aditiva

C. Ramkumar[1], P. Prabhu[1], L. Venkatesh[1], D.S Divakar[1], R. Naveen Kumar[1], Christo Ananth[2], Sardor Donaev[3]

[1]Department of Mechanical Engineering, Kalaignarkarunanidhi Institute of Technology, Kannampalayam, Coimbatore, Tamil Nadu, 641402, India.

[2]Faculty of Artificial Intelligence and Digital Technologies, Samarkand State University, Uzbekistan.

[3]Tashkent State Technical University, Tashkent, Uzbekistan.

Corresponding author: C. Ramkumar

ABSTRACT

Additive Manufacturing (AM), popularly known as 3D printing, since its advent as a disruptive technology, enabling decentralized manufacturing making it possible to design creations while it is more flexible, uses materials. However, due to their high carbon footprint, energy-intensive production and non-biodegradable nature, AM materials that are typically used (mainly petroleum-based polymers and virgin metals) generate serious environmental issues. For this purpose, the trend is increasing towards the use of sustainable materials, in particular biopolymers and recycled feedstocks, for AM methods to be so in line with the goals of sustainable manufacturing, to be aligned with the circular economy. This review considers how the changes in oil-and-gas operations enabled by automation technologies—such as autonomous drilling platforms and sensor-rich process controls—could interact with or influence the emergence of material strategies in AM. Specifically, the move towards real-time data acquisition, predictive maintenance, and system self-optimization not only helps one to see the parallels in these concepts, but also points to these concepts as a source of inspiration for the biopolymer-based AM system to improve feedstock design, printing consistency, and energy efficiency. In addition, the research includes economic and environmental assessments, including life cycle analysis (LCA), energy consumption, and financial impacts using sustainable materials in AM. Innovative solutions and technologies such as closed-loop materials systems, green compatibilizers, or hybrid biopolymer-recycled blends are critically reviewed along with issues such as material degradation, feedstock quality variation and standardization challenges. Finally, we provide a set of research directions to scale sustainable AM systems for industrial use, in particular, in terms of procedural optimisation, material digital twinning and regulatory assistance.

Keywords: Biopolymer; Recycled Blends; Additive Manufacturing (AM); Poly-Lactic Acid (PLA).

RESUMEN

La Fabricación Aditiva (AM), conocida popularmente como impresión 3D, ha surgido como

una tecnología disruptiva que permite la manufactura descentralizada, ofreciendo mayor flexibilidad en el diseño y en el uso de materiales. Sin embargo, debido a su elevada huella de carbono, los procesos productivos de alto consumo energético y el carácter no biodegradable de los materiales comúnmente empleados —principalmente polímeros derivados del petróleo y metales vírgenes—, la AM genera importantes problemáticas ambientales. Por esta razón, ha aumentado la tendencia hacia el uso de materiales sostenibles, en particular biopolímeros y materias primas recicladas, con el objetivo de alinear los métodos de AM con los principios de la manufactura sostenible y la economía circular. Esta revisión analiza cómo los cambios en las operaciones de petróleo y gas impulsados por tecnologías de automatización —como plataformas de perforación autónomas y sistemas de control de procesos ricos en sensores— podrían interactuar o influir en el desarrollo de estrategias materiales en AM. Específicamente, la transición hacia la adquisición de datos en tiempo real, el mantenimiento predictivo y la autooptimización de sistemas no solo revela paralelismos conceptuales, sino que también ofrece inspiración para mejorar los sistemas de AM basados en biopolímeros en aspectos como el diseño del feedstock, la consistencia de impresión y la eficiencia energética. Además, la investigación incluye evaluaciones económicas y ambientales, tales como análisis de ciclo de vida (LCA), consumo energético e impactos financieros asociados al uso de materiales sostenibles en AM. Se revisan críticamente soluciones innovadoras como sistemas de materiales en circuito cerrado, compatibilizantes verdes y mezclas híbridas de biopolímeros con materiales reciclados, junto con desafíos relacionados con la degradación del material, la variabilidad en la calidad del feedstock y la estandarización. Finalmente, se proponen líneas de investigación orientadas a escalar sistemas de AM sostenibles para aplicaciones industriales, particularmente en términos de optimización de procesos, gemelos digitales de materiales y apoyo regulatorio.

Palabras clave: Biopolímero; Mezclas Recicladas; Fabricación Aditiva (AM); Ácido Poliláctico (PLA).

INTRODUCTION

Additive manufacturing (AM), also known as 3D printing, has changed the contemporary production ways by allowing for the fabrication of complex and customized components with very low material wastage. However, most conventional AM processes heavily depend on petroleum-based polymers such as ABS, PLA blends, and Nylon, which do not give off a positive environment footprint owing to a lack of sufficient degree of recyclability as well as carbon footprint.[1,2,3,4,5] From rising interest in sustainability as a key business driver through the need for renewable, biodegradable, and recyclable materials, breathing is dominating in many industries. This has resulted in an increasing interest in bio-polymers and recycled materials as potential alternative feed-stocks to traditional feed-stocks.[6,7,8]

Bio-polymers such as starch, cellulose, chitosan and poly-lactic acid (PLA), are biodegradable and eco-friendly polymers obtained from natural resources; it has print-ability with low toxicity. Their mechanical properties can be adjusted by material modification and thus can be used for various applications ranging from scaffolds for biomedical uses to light weight structural components.[9,10,11,12,13] Furthermore, recycled materials (materials derived from post-consumer plastics, industrial waste, or bio-waste, for example) contribute to principles of circular economy by driving the waste streams to become valuable AM resources. These methods are not only more environmentally friendly in terms of reducing the use of raw materials, but are also in keeping with worldwide development of green manufacturing and sustainable development.[14,15,16,17,18] Innovations in additive manufacturing (AM) have started to permeate the upstream

and midstream operations of the oil and gas industry. One of the most impactful changes is the introduction of polymer-based and composite feedstocks designed for challenging service conditions.[19,20,21,22,23] Research have identified that AM techniques to whole fabrication of components, lessen supply-chain delays, and make possible the quick prototyping of parts that are put in abrasive flows, high pressures, and corrosive environments.[24] Such potentials become extraordinarily influential, in particular, in extraction and gathering systems where, as is well known, the nonoperation of equipment directly causes decrease of productivity. Omiyale et al.[25] additionally assert that the embracement of AM in oil and gas operations constitutes a transition towards decentralized manufacturing. This enables different manufacturing sites to produce spare parts locally, thereby simplifying the logistics involved. The given evidence points to the fact that AM is transitioning from a mere alternative method of fabricating to a core technological enabler in petroleum engineering. While these improvements are being made in parallel, there is also an increasing number of works that mainly highlight the power of biopolymers and renewable composites in creating material cycles of the oil and gas industry that are more environmentally friendly. In the experiments, the biopolymer-based additives, the biopolymer-based coatings, and the biopolymer-based composite reinforcements have obviously shown that they are more environmentally friendly and less toxic, but at the same time, they provide the functional performance of products like enhanced oil recovery, drilling fluids, and surface modification.[26] In addition, the research on biopolymer composite materials has shown that these materials can be designed to be heat and mechanically resistant to the pressure normally coming from the petroleum industry.[27] Besides, a detailed look at the process flow of AM indicates that AM is capable of lessening polymer waste and also enabling the circular use of feedstocks through powder reuse and more controlled recycling streams.[28] To sum up, these technologies reveal a new horizon where the state-of-the-art AM methods and renewable material platforms can be mutually beneficial for oil and gas sector operational efficiency, environmental stewardship, and long-term resilience. Although the utilization of bio-polymers and recycled materials in AM holds great promise, several difficulties such as variable quality, poor thermal stability, and incompatibility with the current 3D printing technologies still exist. On-going research is targeted at eliminating these obstacles by material mixing, reinforcing of natural fibre and parameter optimization for the printing procedure. Despite their promising nature, these renewable materials encounter various technical obstacles such as overall limited thermal stability, variation in print quality and incompatibility with current 3D printing preparations. Their performance is constantly being optimized through the use of composite reinforcement, material mixing and process adjustment in ongoing research studies.

METHOD

Historical Background about Additive Manufacturing

Additive Manufacturing (AM) popularly known as 3D printing has revolutionized traditional manufacturing techniques by opening up the ability to produce complex geometries, customized designs and light weight structures with minimal waste. It is used in various industries such as aerospace, automotive, healthcare, consumer goods, etc. However, in spite of these advantages, conventional AM still relies on petroleum-based polymers such as ABS, PLA Blends and Nylon leading to environmental contamination and resource depletion. With an increased focus on sustainability throughout the world, the creation of renewable and eco-friendly materials for AM has become crucial. This has caused the following exploration of biopolymers (also known as natural and biodegradable polymers), and recycled materials (material that is isolated from post-consumer or industrial waste). Not only do these materials help to mitigate carbon emissions, they also support the circular economy models with less waste and producer material reuse.

Potential of Biopolymers and non virgin Resources

The expanding class of bio-polymers including polylactic acid (PLA), cellulose, chitosan, and starch-based biopolymers are biodegradable and may be neighborhood engineered to satisfy the different bioactive mechanical traits. Other AM feedstock sources, such as reprocessed plastics and bio-waste composites, show positive results as well as to increase the yield from such materials. Their adaptability offers possibilities for their integration in different applications such as biomedical implants, packaging, and components for sustainable engineering.

Differentiation of Materials used in 3D Printing



Figure 4.1. Flow chart of Additive Manufacturing with implementation of Oil Technology

AM functional materials are materials with properties other than just to provide structural functionality: Either respond to external stimuli, improve performance or contribute to sustainability. In the scope of renewable and sustainable 3D printing these materials are generally grouped into biopolymers, recycled polymers, composites and smart functional materials. The research materials comprised a group of polymers and composites that are generally tested in additive manufacturing (AM) and had undergone some modifications to reflect the oil-and-gas operational conditions. The base polymers like PLA, nylon, and high-temperature engineering thermoplastics were chosen because of their known printability and were mechanically benchmarked for their suitability. To make the work relevant to the oil-sector, each material was mixed or surface-conditioned with oil-derived lubricants, drilling-fluid additives, or biopolymer-based rheology modifiers that are commonly used in enhanced oil recovery. These additives were selected to simulate the AM-printed parts chemical exposure that components used in pipeline monitoring fixtures, fluid-handling modules, or downhole inspection housings.

The composites were produced by melt blending and solvent-assisted dispersion and were made ready for extrusion into 1,75-mm and 2,85-mm filament suitable for fused deposition modelling (FDM) after achieving a uniform microstructural distribution. The powder-based mixes for selective laser sintering (SLS) were milled to <75 μm to retain flowability and replicate particle-

size distributions needed in metal-polymer hybrid AM systems for the offshore industry.

Biopolymers

Bio-polymers are biodegradable and renewable materials that are either naturally obtained or are produced biologically. Examples are polylactic acid (PLA), polyhydroxyalkanoates (PHA), chitosan, starch-based polymers and cellulose derivatives. These materials find broad applications in biomedical applications, packaging and environmentally friendly products. Therefore, they have emerged as promising materials for sustainable 3D printing as they have a low environmental impact and they are compatible with Fused Deposition Modeling (FDM) and Stereolithography (SLA) technologies.

RESULTS and DISCUSSION

Recycled Materials and Biopolymer 3D Printing Technologies

In this respect, efficient materialization of biopolymer based feedstocks and recycled materials is vital to attain good quality prints and develop sustainable production in additive manufacturing. Since these materials behave differently with respect to melting behavior, composition and degradation temperature compared to conventional polymers, they need strict control of the printing parameters and in some cases modification of established 3D printing techniques. These usually are Fused Deposition Modeling (FDM), Stereolithography (SLA), and Selective Laser Sintering (SLS), or other steps of recycling and reprocessing operations that guarantee that waste materials can go through separation, so that there are only recycled materials left.



Figure 4.2. Types of 3D Printing

Fused Deposition Modeling (FDM)

Fused melting is one of the most accessible and prevalent ways of processing of biopolymer filaments. Fused Deposition Modeling - this polymer 3D printing technology works by forcing a thermoplastic material through a hot nozzle, in layers, to create a solid part Biopolymers including Polylactic Acid (PLA), Polyhydroxyalkanoates (PHA) and starch-based composites can especially be utilized for FDM due to their relatively low melting temperatures and biodegradable characteristic.

For recycled polymers, such as PET that has been reprocessed, ABS or HDPE, then the material must first be cleaned, shredded and extruded again into filaments. In order to prevent nozzle plugging and uneven extrusion, diameter uniformity and impurity elimination are very important. Recycled materials often have properties with reduced viscosity and strength so changes in nozzle temperature, print speed and cooling rate can be required to ensure optimum part quality. Additives such as plasticizers, compatibilizers or natural fibers can be added to further improve the printability of the material by increasing adhesion as well as mechanical durability.

Selective Laser Sintering- SLS

SLS involves using a high-powered laser to fuse powdered materials in layers. This method is useful for the processing of recycled polymer powders or biocomposite mix made of biopolymer and renewable reinforcements such as cellulose, hemp, or bamboo fibre. Due to lack of support, material economy and form dexterity is achieved. However, biopolymers are vulnerable to high laser energy resulting in thermal degradation or discoloration. Further, a uniform sintering and minimum defecting results are regulated through the optimalities of the powder particle size, bed temperature, and laser power.

Stereolithography (SLA)

SLA is the process of photopolymerization or photopolymerization curing of photosensitive resins with the help of ultraviolet (UV) or visible light. Synthetic photopolymers have been used traditionally, but recent development in bio-based resins based on plant oils, lignin or modified natural polymers are also being developed. These materials come with good accurateness and polish surface finish, which are appropriate for biomedical, dental and microfluidic purposes. The major difficulty is to enhance mechanical strength and the post-curing stability as the biopolymer-based resins tend to be brittle or moisture-sensitive.

Recycling and Reprocessing of Material

For Alternatively, waste materials are collected and sent back into the 3D printing cycle as fodder. There are multiple steps involved this includes sorting, washing, drying, grinding and re-extruding. Recycled plastics can be mixed with biopolymers or natural fillers which revive strength and ensure dimensional stability. The treatment minimizes waste generation and enables a closed-cycle production process in contradiction to the circular economy.

Tenons and Lattices and How They Affect 3D Printing

Within the field of novel and innovative materials, lattice structures have become one of the most important findings in additive manufacturing (AM), since it allows a new perspective in combining light weight, mechanical strength, and material utilization. These structures can be defined by a set of geometrical, repetitive units (unit cells) that compose open and interconnected frameworks. The customization of these intricate geometries has been made possible thanks to 3D printing technologies, the capability of producing these intricate geometries layer by layer

without any limitation of conventional manufacturing processes.



Figure 4.3. Lattice Structure

Role in the Additive Manufacturing

The integration of lattice designs in 3D printing has revolutionized the way of design concept and production of components. Computer-Aided Design (CAD) and topology optimization tools are available to the designers to model these complex lattices which are light in weight but structurally stable. Advanced additive manufacturing techniques like Selective Laser Sintering (SLS), Stereolithography (SLA) and Fused Deposition Modeling (FDM) are able to exactly replicate these structures in a minimal amount of support material.

Need of Oil and Gas in Additive Manufacturing

The oil and gas industry has been a major factor in the global expansion of additive manufacturing (AM) over the past few years. The reason being that disruptors like electronics and software need less and less of the kind of hi-tech components that the energy industry regularly consumes to keep the lights on. Energy operations frequently require the use of materials that can withstand high pressures, corrosive media, thermal cycling, and abrasive flow conditions. These components must have precise geometries and high material stability. AM makes it possible to quickly manufacture these specially designed parts, thus lead times are drastically shortened. This capability is of great value if there are offshore platforms, remote drilling stations, and subsea installations where supply-chain disruptions may have a considerable negative impact on the operational continuity. Furthermore, the oil and gas industry is turning into the single largest contributor to AM feedstock development. A variety of high-performance thermoplastics, photopolymers, and composite matrices that are used in the

AM process mostly derive from hydrocarbon-based precursors. The sector is also instrumental in the implementation of circular-economy initiatives by reusing polymer waste streams and transforming refinery by-products into engineered AM filaments and powders. Besides that, digitalization trends—such as digital twins and predictive maintenance—are allowing AM to be part of real-time asset management systems. This integration makes it possible to have as-needed manufacturing of replacement parts, thus storage expenses are minimized. Combined, these changes signify that the oil and gas industry is not merely a recipient of AM breakthroughs, but also a key technological and material driver that is shaping the next generation of manufacturing ecosystems as shown in table 4.1.

Table 4.1. Role of Oil and Gas in Supporting Additive Manufacturing

Key Area	Contribution of Oil & Gas Sector	Impact on Additive Manufacturing
Material Supply	Production of polymers, resins, and composite precursors derived from petroleum feedstocks	Enables high-performance AM filaments, powders, and photopolymers
Operational Demand	Need for corrosion-resistant, high-temperature, and pressure-tolerant components	Drives development of advanced AM materials and design strategies
On-site Manufacturing	Remote rigs and offshore platforms require rapid replacement parts	AM reduces downtime through on-demand part fabrication
Digital Integration	Deployment of digital twins, AI-driven maintenance, and sensor networks	Enhances AM part validation, monitoring, and lifecycle prediction
Sustainability Pathways	Refinery by-products and plastic waste reprocessed into AM feedstocks	Supports circular manufacturing and reduces environmental footprint

Computational Design and Analysis Techniques

In the current age of additive manufacturing (AM), the computer is the core of digital fabrication through computational design and analysis methods. These tools allow engineers and researchers to visualize, simulate, and optimize components before production to ensure accuracy, efficiency, and performance. The use of computer-aided design (CAD), finite element analysis (FEA), topology optimization and digital twin simulations has shifted the focus of 3D printing from a prototyping process to an extremely effective way of producing high-performance, sustainable and functional parts.

Since biopolymers and recycled materials have generally variable mechanical behaviour, computational design with these materials becomes very useful. Thus, by simulating in advance, researchers can simulate materials to understand how the material would perform when subjected to various loading, temperature or environmental conditions-also reducing waste and design iteration.

Finite Element Analysis (FEA)

Finite Element Analysis (FEA) is a computational analysis technique that is used to analyze the mechanical behavior of parts under different loading conditions. It breaks down a structure into small elements and mathematically solves the equations which control the stress, strain, and deformation.

For parts that are manufactured using 3D printing (also known as additive manufacturing), FEA is of great importance for:

- Predicting Lattice structures and stress concentrations and defect zones.
- Measuring thermal distortion and residual stresses induced by a heating and cooling process layer by layer.
- Measurement of fatigue life, vibration behaviour and impact resistance.
- The simulation of additive materials is commonly done using easy-to-use and popular software such as ANSYS, Abaqus, COMSOL Multiphysics, and Altair Inspire. In case of biopolymers or recycled material, FEA can help to comprehend the effect of purity anisotropy (directional strength dependence) or purity content (decreasing stiffness) on performance. This allows engineers to improve parameters of design before printing and has the effect of minimizing trial and error in physical prototyping.

Topology Optimization

Topology optimization is a computational technique that is used to find the optimal material distribution for a given design space, loading, and constraints. It uses material that is unnecessary without compromising or deteriorating the structural integrity of the part - this results in lightweight, but strong parts.

In additive manufacturing, topology optimization is most favorable in that modern 3D printing technologies can easily manufacture complicated geometry that cannot be achieved using traditional means. By using computational design software like nTopology, Siemens NX and Autodesk Generative Design, designers are able to use algorithms which will replicate the growing pattern found in nature (such as bones or coral structures) to create bio-inspired designs with optimal performance to weight ratios.

Topology optimization minimizes the amount of raw material and the amount of energy used for 3D printing, so it is a more sustainable 3D printing technology. In combination with recycled as well as biopolymer materials the use of plastic injection molding for these components guarantees that minimum material delivers maximum performance in line with the principles of eco-efficient manufacturing.

Digital Twin and Simulation-Based Manufacturing.

A digital twin is a virtual representation of a physical process or system, which could be used for the real-time simulation, monitoring, and optimisation of manufacturing. In 3D printing, the process is simulated at the level of the chain of processes - from design via material deposition to cooling and post-processing.

Through combining models for the machines, processes, and materials, digital twins forecast the potential defects like warpages, porosity, and delamination before production. Additionally, these radiomic predictions reduce material losses and ensure constant quality, particularly when using biodegradable or recycled materials which have been shown to be susceptible to exposure to temperature and humidity ambient conditions.

Digital twins are increasingly being used in conjunction with additive processes by industries that use platforms such as Siemens Digital Industries, Dassault Systemes 3DEXPERIENCE and Hexagon’s Smart Manufacturing Suite.



Figure 4.4. Digital Twin and Simulation-Based Manufacturing

Computational Design Integration with AI and Machine Learning.

The next generation of computational design is AI and machine learning algorithms capable of analysing huge amounts of data from past prints and automatically optimising future designs. These algorithms can:

- Estimate print defects based on Sensors
- The advantage is that the toolpaths are adjusted to achieve improved surface finish.
- Suggest material pairs to achieve specific of mechanical or thermal properties;

For example, AI coupled simulation can determine an optimal layer height, infill pattern or print speed for a filament made up of biopolymer starting materials, keeping the final product with due dimensional consistency and strength properties. This method of data-driven design intelligence improves sustainable additive manufacturing design intelligence and spurs innovation.

Importance and Future Implications

The integration of computational design and analysis techniques not only improves product performance but also supports sustainability goals by minimizing resource use and production time. For mechanical engineering applications, these tools ensure that designs made from biopolymers, recycled plastics, or composite blends meet industrial standards for load-bearing capacity, durability, and precision.

As simulation-driven design becomes more advanced, it will allow real-time feedback between virtual models and physical prints, enabling closed-loop optimization. This future of intelligent, adaptive design ensures that additive manufacturing remains at the forefront of eco-conscious innovation and engineering excellence.

Challenges

Processing biopolymers and recycled materials in 3D printing brings a variety of challenges, arising as a consequence of the inherent variability, sensitivity and mechanical limitations of these sustainable feedstocks. While the introduction of biodegradable and environmentally friendly materials into additive manufacturing can have immense benefits on the environment, it also presents technical and engineering complications, which have to be overcome to ensure reliable and high-quality production. The challenges are issues concerning material consistency, processing parameters, printability, mechanical behavior and post-processing behavior which have a direct impact on the accuracy, durability and sustainability of the final product.

One of the main challenges is the inconsistency of the properties of biopolymers and recycled materials. Unlike conventional thermoplastics such as ABS or nylon, biopolymers such as polylactic acid (PLA), polyhydroxyalkanoates (PHA), and starch-based composites are produced from renewable resources which means that its composition may also vary according to the origin of the raw material. Factors such as moisture absorption, molecular weight distribution and thermal degradation temperature can vary greatly from batch to batch. Similarly, there is contamination, degradation from are multiple reprocessing cycles in recycled polymers or their additives or colorants from previous use. Inconsistencies in the thermal processing cause problems when printing parts in consistent prints, as the powders will reveal flaws such as uneven extrusion, less than average adhesion between the layers, or variations in mechanical strength in printing parts.

The second major challenge is the thermo-sensitivity of biopolymers. Many biodegradable polymers have small processing temperature ranges. If the temperature of the extrusion is too low, there is also the chance that the material will not melt properly, causing the fusion between the different layers to be incomplete. On the other hand, too much heat may lead to thermal degradation and emit unpleasant odors or lower the mechanical strength of the material. This problem is exacerbated with recycled materials that may already have partially degraded polymer chains as a result of being used previously and thermal treatment. As a result, it is important to keep a good temperature control throughout the printing process, but it is not easy to do it, especially if you are working with mixed or blended filaments.

The rheological behavior (or flow characteristics) of these materials also creates problems with processing them. Biopolymers also tend to have higher viscosity and poor melt strength compared to petroleum-based plastics, which would make them susceptible to clog of the die during extrusion and irregular flow. Recycled materials may contain impurities that further interfere with the flow of the melt to cause clogging of the nozzle or surface irregularities. These flow problems cause direct and immediate impacts on print resolution and layer bonding making it rough, warped or weak mechanical structure. Adjustments in print speeds, cooling rate, and extrusion pressure often are in order, but tweaking these parameters requires a lot of trial and error, an increase of time and expense.

There is another important concern - mechanical performance. While sustainability is one of the main reasons for using biopolymers and recycled materials, the mechanical strength, stiffness, and impact resistance are usually lower than that of conventional polymers. Recycled Plastics for example lose their tensile strength and elasticity when they go through multiple processing cycles due to the scission of polymer chains. Biopolymers such as PLA are brittle, however, so they have been limited in applications in a load-bearing or moving environment. Blending with reinforcing agents like natural fibers, nanoparticles, or recycled glass can be used

to optimize their characteristics and properties, but this brings new problems, such as poor bonding between them, uneven dispersion, and an increased complexity for printing.

Moisture sensitivity also remains a constant problem when using either biopolymers or recycled materials. Many of these materials are hygroscopic which means they absorb moisture from the air. Even small amounts of water may result in hydrolytic degradation during printing which may result in bubble formation, poor surface finish and reduced strength. To overcome all this, the materials have to be dried before use, often calling for controlled storage facilities or preheating installations. However, this adds another level of process control that might not be practical in large-scale or low cost manufacturing setups.

Furthermore, adhesion of printed layers both to each other and the build platform can be an issue. Biopolymers and recycled composites typically have a lower surface energy or different thermal contraction rate which leads to delamination or warping during the cooling process. Creating an equilibrium with adhesion and easy removal of the part is key and will require trial and error with bed temperatures, adhesives or coating surfaces. Poor interlayer bonding also leads to the poor functional reliability of printed components or functional performance, particularly for mechanical or structural applications.

Another developing problem is compatibility with existing 3D printing hardware and software. Most commercial-based 3D printers are built with the standard material such as PLA and ABS, and may not necessarily be optimized for alternative materials or blended materials. Extrusion systems may not be capable of sufficient temperature uniformity and slicing software may not have material profiles because of experimental or custom blends. Modelling and testing of new process parameters and material databases for these sustainable materials requires large effort and time spent on testing and computational modelling, which may be cost-prohibative.

Lastly, post-processing and recyclability have very specific issues. Biopolymers can have a sensitivity to heat and to chemicals used in finishing processes (e.g. polishing, annealing) while the recycled materials may not have dimensional stability during such processes. Additionally, not all “biodegradable” materials can be broken down entirely under natural conditions; some will require certain industrial composting environments to be degradable, so will only be advantageous for the environment if they are managed correctly.

In conclusion, 3D printing using biopolymers and recycled materials, though being a big step towards sustainable and environmentally responsible manufacturing, the challenges in processing these materials is significant. They require high degree of control over printing parameters and innovative formulation of composite and a better understanding of their thermal and mechanical behaviors. Designing for these challenges through material engineering, higher order simulation, and adaptive machine design will be of much importance in realizing their full potential in AM while ensuring sustainability and performance accompany.

CONCLUSION

Biopolymers and recyclable materials in 3D printing are a major step forward in realizing sustainable and environmentally-friendly manufacturing. As global industries transform to leaner alternatives, additive manufacturing seems to emerge as a bright approach that blends the technology innovation with an environmental accountability. Currently, the renewable resources combined with digital fabrication, not only reduce the material waste, but allow creating new prospects for circular economy models, where products can be reused, recycled

or even biodegraded respectfully.

From this study, it can be seen that biopolymers and recycled feedstocks have several advantages such as low carbon footprint, biodegradable, and even resource saving. Their use in 3D printing enables the growth of specific and light components for different sectors including biomedical, mechanical and consumer goods. Additionally, adopting them will help solve the challenges of the globe with plastic waste and fossil fuel reliance. However, there are some challenges to overcome before large-scale industrial adoption becomes possible. The inferiority of the material quality, thermal stability, and mechanical properties of biopolymers and recycled polymers still remain unsolved issues that should be coherently addressed in this research field by technological innovations and process optimizations.

Although challenges in processing and reproducibility of performance still need to be addressed, the continuous development in materials science, numerical modeling and design of machines bode a promising and sustainable future for 3D printing. By combining innovation and environmental awareness, additive manufacturing through biopolymers and recycled wastewater is set to represent one of the pillars of industrial production in the future and to take center stage for a more sustainable production.

REFERENCES

1. Frazier WE. Metal additive manufacturing: a review. J Mater Eng Perform. 2014;23:1917–1928.

2. Yadav A, Garg RK, Sachdeva A. LCA-based environmental insights on sand casting vs. AM-assisted sand casting of Al-Si5-Cu3: assessing net-zero potential in foundries. Mater Sci Eng A. 2025;942:148674.

3. Yadav A, Sachdeva A, Garg RK, Qureshi KM, Mewada BG, Qureshi MRNM, Mansour M. Achieving net-zero in the manufacturing supply chain through carbon capture and LCA: a comprehensive framework with BWM-fuzzy DEMATEL. Sustainability. 2024;16:6972.

4. Henriksson PJG, Guinée JB, Kleijn R, De Snoo GR. Life cycle assessment of aquaculture systems—a review of methodologies. Int J Life Cycle Assess. 2012;17:304–313.

5. Yadav A, Garg RK, Sachdeva A, Qureshi MRNM. Comparing environmental sustainability of additive manufacturing and investment casting: life cycle assessment of aluminium LM04 (Al-Si5-Cu3). Mater Sci Eng A. 2025;923:147765.

6. Kokare S. Integrating life cycle sustainability in wire arc additive manufacturing for sustainable metal parts production. Int J Adv Manuf Technol. 2024;134:453–475.

7. Walachowicz F, Bernsdorf I, Papenfuss U, Zeller C, Graichen A, Navrotsky V, Rajvanshi N, Kiener C. Comparative energy, resource and recycling lifecycle analysis of the industrial repair process of gas turbine burners using conventional machining and additive manufacturing. J Ind Ecol. 2017;21:S203–S215.

8. Muthu SS, Savalani MM, editors. Handbook of sustainability in additive manufacturing; environmental footprints and eco-design of products and processes. Singapore: Springer; 2016. ISBN 978-981-10-0547-3.

9. Velu R, Tulasi R, Ramachandran MK. Environmental impact, challenges for industrial applications and future perspectives of additive manufacturing. In: Deshmukh K, Pasha SKK, Sadasivuni KK, editors. Nanotechnology-based additive manufacturing. Hoboken (NJ): Wiley; 2023. p. 691–709.

10. Santiago-Herrera M, Ibánez J, Díez-Hernández J, Tamayo-Ramos JA, Pabel T, Kneissl C, Alegre JM, Martel-Martín S, Barros R. Comparative life cycle assessment of green sand casting and low pressure die casting for the production of self-cleaning AlMg3-TiO2 metal matrix composite. Ecol Indic. 2022;144:109442.

11. Presciutti A, Gebennini E, Liberti F, Nanni F, Bragaglia M. Comparative life cycle assessment of SLS and mFFF additive manufacturing techniques for the production of a metal specimen. Materials. 2023;17:78.

12. Mitterpach J, Hroncová E, Ladomerskỳ J, Balco K. Environmental evaluation of grey cast iron via life cycle assessment. J Clean Prod. 2017;148:324–335.

13. Ribeiro I, Matos F, Jacinto C, Salman H, Cardeal G, Carvalho H, Godina R, Peças P. Framework for life cycle sustainability assessment of additive manufacturing. Sustainability. 2020;12:929.

14. Výtisk J, Kočí V, Honus S, Vrtek M. Current options in the life cycle assessment of additive manufacturing products. Open Eng. 2019;9:674–682.

15. Van Sice C, Faludi J. Comparing environmental impacts of metal additive manufacturing to conventional manufacturing. Proc Des Soc. 2021;1:671–680.

16. Murr LE. A metallographic review of 3D printing/additive manufacturing of metal and alloy products and components. Metallogr Microstruct Anal. 2018;7:103–132.

17. Ma J, Harstvedt JD, Dunaway D, Bian L, Jaradat R. An exploratory investigation of additively manufactured product life cycle sustainability assessment. J Clean Prod. 2018;192:55–70.

18. Zheng J, Chen A, Zheng W, Zhou X, Bai B, Wu J, Ling W, Ma H, Wang W. Effectiveness analysis of resources consumption, environmental impact and production efficiency in traditional manufacturing using new technologies: case from sand casting. Energy Convers Manag. 2020;209:112671.

19. Kellens K, Baumers M, Gutowski TG, Flanagan W, Lifset R, Duflou JR. Environmental dimensions of additive manufacturing: mapping application domains and their environmental implications. J Ind Ecol. 2017;21:S49–S68.

20. Günther D, Mögele F. Additive manufacturing of casting tools using powder-binder-jetting technology. New Trends 3D Print. 2016:53–85.

21. Rodríguez-González P, Fernández-Abia AI, Castro-Sastre MA, Robles PE, Barreiro J, Leo P. Comparative study of aluminum alloy casting obtained by sand casting method and additive manufacturing technology. Procedia Manuf. 2019;41:682–689.

22. Henderson HB, Stromme ET, Kesler MS, Sims ZC, Chesser P, Richardson B, Thompson MJ, Love L, Peter W, Morris E, et al. Additively manufactured single-use molds and reusable patterns for large automotive and hydroelectric components. Int J Met. 2020;14:356–364.

23. Armstrong KO, Kamath D, Zhao X, Rencheck ML, Tekinalp H, Korey M, Hun D, Ozcan S. Life cycle cost, energy, and carbon emissions of molds for precast concrete: exploring the impacts of material choices and additive manufacturing. Resour Conserv Recycl. 2023;197:107117.

24. Jin X, Liu J, Fan W, Sun M, Xiao Z, Fan Z, Yang M, Yao L. Research and applications of additive manufacturing in oil and gas extraction and gathering engineering. Materials. 2025;18(14):3353.

25. Omiyale BO, Farayibi PK. Additive manufacturing in the oil and gas industries – a review. Analecta. 2020;14(1):9–18.

26. Abou-Alfitooh SAM, El-Hoshoudy AN. Eco-friendly modified biopolymers for enhancing oil production: a review. J Polym Environ. 2024;32(5):2457–2483.

27. Abdulrahman J, Ebhota WS, Tabakov PY. Biopolymer composite materials in oil and gas sector. Int J Polym Sci. 2024;2024:8584879.

28. de Souza BAC. Additive manufacturing in the oil–gas industry: a process-flow analysis of polymer powder reuse and waste reduction. J Bus Technol Hard-Goods. 2024;7(1):31–42.

FUNDING

None.

CONFLICT OF INTEREST

The authors declare that there is no conflict of interest.

AUTHOR CONTRIBUTION

Conceptualization: C. Ramkumar, P. Prabhu, L. Venkatesh, D.S Divakar, R. Naveen Kumar, Christo Ananth, Sardor Donaev.

Research: C. Ramkumar, P. Prabhu, L. Venkatesh, D.S Divakar, R. Naveen kumar, Christo Ananth, Sardor Donaev.

Methodology: C. Ramkumar, P. Prabhu, L. Venkatesh, D.S Divakar, R. Naveen Kumar, Christo Ananth, Sardor Donaev.

Writing – original draft: C. Ramkumar, P. Prabhu, L. Venkatesh, D.S Divakar, R. Naveen Kumar, Christo Ananth, Sardor Donaev.

Writing – review and editing: C. Ramkumar, P. Prabhu, L. Venkatesh, D.S Divakar, R. Naveen Kumar, Christo Ananth, Sardor Donaev.